



RIDER TOWN 4T 20W-50

Description

Refined lubricant oil especially designed for 4-stroke petrol engine motorcycles the greater part of whose activity is developed in an urban environment. Its additives prolong its life in this type of working conditions.

Properties

- Guarantees good lubrication in normal service conditions.
- Prevents the formation of lacquers and varnishes thanks to its dispersant additives.
- Its degree of viscosity guarantees perfect performance in warm atmospheres.
- Its detergency ensures the piston is properly cleaned.
- It maintains an adequate pressure and temperature under all service conditions.

Quality levels, approvals and recommendations

• JASO: MA2*

• API: SJ

*Formal approval

Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			20W-50
Density at 15 °C	g/cm ³	ASTM D4052	0.892
Viscosity at 100 °C	cSt	ASTM D445	18
Viscosity at 40 °C	cSt	ASTM D445	170
Viscosity at -15 °C	cP	ASTM D5293	<9,500
Viscosity index	-	ASTM D2270	119
Flash point, open cup	°C	ASTM D92	250
Pour point	°C	ASTM D97	-36
TBN	mg KOH/g	ASTM D2896	5.7
Viscosity at 100 °C after shear	cSt	CEC L-14-93	>15
NOACK volatility	% in weight	ASTM D5800	7.3

The above mentioned characteristics are typical values and should not be considered product specifications.